





WELDED TUBE OF CANADA  
 MILL CAPABILITY ALL DIVISIONS  
 MCAD SP 7.3 SEPTEMBER 9,2006 REV 1  
 1-800-565-8823

**WALL THICKNESS**

GAUGE	20	19	18	16	15	14	13	12	11	10	9	8	7	3/16	1/4	5/16	3/8	1/2	
<b>SHAPES * WELD POSITION AVAILABLE ON BOTH SIDES</b>	<b>0.035"</b>	<b>0.042"</b>	<b>0.049"</b>	<b>0.065"</b>	<b>0.072"</b>	<b>0.083"</b>	<b>0.095"</b>	<b>0.109"</b>	<b>0.120"</b>	<b>0.134"</b>	<b>0.148"</b>	<b>0.165"</b>	<b>0.180"</b>	<b>0.188"</b>	<b>0.250"</b>	<b>0.313"</b>	<b>0.375"</b>	<b>0.500"</b>	
	<b>**Weight per Foot lb/ft</b>																		
<b>2.000 x 1.250</b>		0.89	1.03	1.34	1.48	1.68	1.9	2.15	2.33	2.56									
<b>2.000 x 2.000</b>		1.10	1.28	1.68	1.84	2.11	2.38	2.7	2.94	3.25	3.54	3.88	4.18	4.33	5.41				
<b>2.000 x 3.000*</b>				2.12	2.33	2.67	3.03	3.44	3.76	4.16	4.55	5.01	5.4	5.61	7.11	8.46			
<b>2.173 x 2.173</b>						2.3	2.61	2.96	3.23	3.56	3.89	4.27	4.6	4.77					
<b>2.362 x 1.575</b>				1.65	1.81	2.07	2.34	2.66	2.89	3.19									
<b>2.362 x 2.362</b>								3.24	3.54	3.91	4.27	4.7	5.06	5.25	6.64				
<b>2.500 x 1.000</b>				1.45	1.6	1.82	2.06	2.33	2.54										
<b>2.500 x 2.000*</b>						2.39	2.71	3.07	3.35	3.7	4.04	4.44	4.79	4.97					
<b>2.500 x 2.500</b>			1.61	2.12	2.33	2.67	3.03	3.44	3.76	4.16	4.55	5.01	5.4	5.61	7.11	8.46			
<b>2.500 x 3.000*</b>						2.95	3.35	3.81	4.17	4.61	5.05	5.57	6.01	6.25	7.96	9.53			
<b>2.500 x 3.500*</b>						3.24	3.68	4.19	4.58	5.07	5.55	6.13	6.63	6.89	8.81	10.59			
<b>2.530 x 2.530</b>								3.49	3.81	4.21	4.61	5.07	5.47	5.68	7.21	8.59			
<b>2.569 x 2.569</b>						2.75	3.12	3.55	3.87	4.28	4.69	5.16	5.57	5.78					
<b>2.625 x 2.625</b>						2.81	3.19	3.63	3.97	4.39	4.8	5.29	5.71	5.93					
<b>3.000 x 1.000</b>				1.68	1.84	2.11	2.38	2.7	2.94	3.25	3.54	3.88	4.18	4.33					
<b>3.000 x 1.500</b>				1.90	2.09	2.39	2.71	3.07	3.35	3.7	4.04	4.44	4.79	4.97					
<b>3.000 x 3.000</b>						3.24	3.68	4.19	4.58	5.07	5.55	6.13	6.63	6.89	8.81	10.59			
<b>3.031 x 3.031</b>								4.23	4.63	5.13	5.62	6.2	6.7	6.97	8.92	10.72			
<b>3.150 x 3.937</b>								4.99	5.47	6.06	6.65	7.35	7.96	8.28	10.66	12.91			
<b>3.500 x 1.500</b>						2.67	3.03	3.44	3.76	4.16	4.55	5.01	5.4	5.61					
<b>3.500 x 2.000</b>								3.81	4.17	4.61	5.05	5.57	6.01	6.25	7.96	9.53			
<b>3.500 x 3.500</b>						3.8	4.32	4.93	5.4	5.98	6.56	7.25	7.85	8.17	10.51	12.72			
<b>3.750 x 1.100</b>						2.59	2.93	3.33	3.64	4.02	4.4	4.84	5.22	5.42					
<b>3.875 x 2.000</b>						3.16	3.6	4.09	4.48	4.96	5.43	5.99	6.47	6.73					
<b>3.875 x 3.875</b>								5.48	6.01	6.67	7.32	8.09	8.77	9.13					
<b>3.937 x 4.724</b>									6.75	7.5	8.23	9.12	9.89	10.29	13.34	16.26			
<b>4.000 x 1.500</b>						2.95	3.35	3.81	4.17	4.61	5.05	5.57	6.01	6.25					
<b>4.000 x 2.000*</b>						3.24	3.68	4.19	4.58	5.07	5.55	6.13	6.63	6.89	8.81	10.59			
<b>4.000 x 2.000*</b>							3.68	4.19	4.58	5.07	5.55	6.13	6.63	6.89					



WELDED TUBE OF CANADA  
 MILL CAPABILITY ALL DIVISIONS  
 MCAD SP 7.3 SEPTEMBER 9,2006 REV 1  
 1-800-565-8823

**WALL THICKNESS**

GAUGE	WALL THICKNESS																		
	20	19	18	16	15	14	13	12	11	10	9	8	7	3/16	1/4	5/16	3/8	1/2	
<b>SHAPES * WELD POSITION AVAILABLE ON BOTH SIDES</b>	<b>0.035"</b>	<b>0.042"</b>	<b>0.049"</b>	<b>0.065"</b>	<b>0.072"</b>	<b>0.083"</b>	<b>0.095"</b>	<b>0.109"</b>	<b>0.120"</b>	<b>0.134"</b>	<b>0.148"</b>	<b>0.165"</b>	<b>0.180"</b>	<b>0.188"</b>	<b>0.250"</b>	<b>0.313"</b>	<b>0.375"</b>	<b>0.500"</b>	
	<b>**Weight per Foot lb/ft</b>																		
4.000 x 2.500*						3.52	4	4.56	4.99	5.53	6.06	6.69	7.24	7.53	9.66	11.66			
4.000 x 3.000						3.8	4.32	4.93	5.4	5.98	6.56	7.25	7.85	8.17	10.51	12.72			
4.000 x 3.500*									5.8	6.44	7.07	7.81	8.46	8.81	11.36	13.79			
4.000 x 4.000									6.21	6.89	7.57	8.38	9.08	9.45	12.21	14.85	17.27	21.63	
4.500 x 2.500						3.8	4.32	4.93	5.4	5.98	6.56	7.25	7.85	8.17	10.51	12.72			
4.500 x 3.00*									5.8	6.44	7.07	7.81	8.46	8.81	11.36	13.79			
4.500 x 4.500									7.03	7.81	8.58	9.5	10.3	10.73	13.92	16.98	19.83	25.04	
5.000 x 2.000						3.8	4.32	4.93	5.4	5.98	6.56	7.25	7.85	8.17	10.51	12.72			
5.00 x 2.500*									5.8	6.44	7.07	7.81	8.46	8.81	11.36	13.79			
5.000 x 3.000*									6.21	6.89	7.57	8.38	9.08	9.45	12.21	14.85	17.27	21.63	
5.000 x 4.000*									7.03	7.81	8.58	9.5	10.3	10.73	13.92	16.98	19.83	25.04	
5.000 x 5.000									7.85	8.72	9.58	10.62	11.53	12.01	15.62	19.11	22.38	28.44	
5.480 x 4.605									7.92	8.8	9.67	10.72	11.63	12.11	15.76	19.29			
6.000 x 2.000*									6.21	6.89	7.57	8.38	9.08	9.45	12.21	14.85	17.27	21.63	
6.000 x 3.000*									7.03	7.81	8.58	9.5	10.3	10.73	13.92	16.98	19.83	25.04	
6.000 x 4.000*									7.85	8.72	9.58	10.62	11.53	12.01	15.62	19.11	22.38	28.44	
6.000 x 5.000*														13.29	17.32	21.24	24.93	31.84	
6.000 x 6.000														14.56	19.02	23.37	27.48	35.24	
7.000 x 2.000									7.03	7.81	8.58	9.5	10.3	10.73	13.92	16.98	19.83	25.04	
7.000 x 3.000*									7.85	8.72	9.58	10.62	11.53	12.01	15.62	19.11	22.38	28.44	
7.000 x 4.000*														13.29	17.32	21.24	24.93		
7.000 x 5.000*														14.56	19.02	23.37	27.48	35.24	
7.000 x 6.000*														15.84	20.72	25.50	30.04		
7.000 x 7.000														17.12	22.42	27.63	32.59	42.05	
8.000 x 2.000									7.85	8.72	9.58	10.62	11.53	12.01	15.62	19.11	22.38	28.44	
8.000 x 3.000*														13.29	17.32	21.24	24.93		
8.000 x 4.000*														14.56	19.02	23.37	27.48	35.24	
8.000 x 5.000*														15.84	20.72	25.50	30.04	38.65	
8.000 x 6.000*														17.12	22.42	27.63	32.59	42.05	



WELDED TUBE OF CANADA  
 MILL CAPABILITY ALL DIVISIONS  
 MCAD SP 7.3 SEPTEMBER 9,2006 REV 1  
 1-800-565-8823

**WALL THICKNESS**

GAUGE	20	19	18	16	15	14	13	12	11	10	9	8	7	3/16	1/4	5/16	3/8	1/2
<b>SHAPES * WELD POSITION AVAILABLE ON BOTH SIDES</b>	<b>0.035"</b>	<b>0.042"</b>	<b>0.049"</b>	<b>0.065"</b>	<b>0.072"</b>	<b>0.083"</b>	<b>0.095"</b>	<b>0.109"</b>	<b>0.120"</b>	<b>0.134"</b>	<b>0.148"</b>	<b>0.165"</b>	<b>0.180"</b>	<b>0.188"</b>	<b>0.250"</b>	<b>0.313"</b>	<b>0.375"</b>	<b>0.500"</b>
	<b>**Weight per Foot lb/ft</b>																	
<b>8.000 x 8.000</b>														19.68	25.83	31.89	37.69	48.86
<b>9.000 x 3.000</b>														14.56	19.02	23.37	27.48	
<b>9.000 x 5.000</b>														17.12	22.42	27.63	32.59	42.05
<b>9.000 x 7.000</b>														19.68	25.83	31.89	37.69	48.86
<b>10.000 x 2.000</b>														14.56	19.02	23.37		
<b>10.000 x 3.000</b>														15.84	20.72	25.50	30.04	
<b>10.000 x 3.500</b>														16.48	21.57	26.57	31.31	40.35
<b>10.000 x 4.000</b>														17.12	22.42	27.63	32.59	42.05
<b>10.000 x 6.000</b>														19.68	25.83	31.89	37.69	48.86
<b>12.000 x 2.000</b>														17.12	22.42	27.63		
<b>12.000 x 3.000</b>														18.40	24.13	29.76		
<b>12.000 x 3.500</b>														19.04	24.98	30.83	36.42	
<b>12.000 x 4.000</b>														19.68	25.83	31.89	37.69	48.86

SPECIFICATIONS PRODUCED TO: ASTM A-500, A-513, A53, CSAG40.21, API 5L, 5CT, CSA Z245.01  
 OTHER GRADES AND SPECIFICATIONS UPON REQUEST.

\*\* ABOVE TABLE VALUES ARE FOR REFERENCE PURPOSES ONLY.

ON TIME QUALITY PRODUCTION SAFELY  
 To improve or modify this controlled document please use form CR SP 4.2.3.